



SAFETY DATA SHEET
Shellac Sanding Sealer

According to Regulation (EC) No 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME Shellac Sanding Sealer
 APPLICATION Air drying paint/lacquer product for interior use
 SUPPLIER Chestnut Products
 PO BOX 536
 Ipswich
 IP4 5WN
 Tel. +44 (0) 1473 425878
 Fax. + 44 (0) 1473 431096
 CONTACT PERSON mailroom@chestnutproducts.co.uk
 EMERGENCY TELEPHONE + 44 (0) 1473 425878 (09:00 - 17:00 Mon to Fri)

2 HAZARDS IDENTIFICATION

Highly flammable. Harmful by inhalation, in contact with skin and if swallowed. Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.
 CLASSIFICATION Xn;R20/21/22, R68/20/21/22. F;R11.

PHYSICAL AND CHEMICAL HAZARDS

The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

HUMAN HEALTH

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
AMYL ALCOHOL (EXCEPT tert-PENTANOL)	250-378-8	30899-19-5	0-2.5%	R10 Xn;R20 Xi;R37 R66
ETHANOL	200-578-6	64-17-5	50-100%	F;R11
METHANOL	200-659-6	67-56-1	2.5-10%	F;R11 T;R23/24/25,R39/23/24/25
SOLVENT NAPHTHA(PETROLEUM),LIGHT AROMATIC	265-199-0	64742-95-6	0-2.5%	Xn;R65.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Get medical attention. NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS!

INHALATION

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

Shellac Sanding Sealer

INGESTION

Immediately rinse mouth and provide fresh air. DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Wash skin with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Immediately rinse with water. Continue to rinse for at least 15 minutes. Make sure to remove any contact lenses from the eyes before rinsing. Get medical attention promptly if symptoms occur after washing.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Foam, carbon dioxide or dry powder.

SPECIAL FIRE FIGHTING PROCEDURES

Do not use water jet as an extinguisher, as this will spread the fire.

UNUSUAL FIRE & EXPLOSION HAZARDS

Cool containers exposed to flames with water until well after the fire is out. Dike and collect extinguishing water.

SPECIFIC HAZARDS

Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO2).

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains. The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Provide ventilation and confine spill. Do not allow runoff to sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Use only in well-ventilated areas. Contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in hazardous vapour concentrations. Take precautionary measures against static discharges. Ground container and transfer equipment to eliminate static electric sparks. Anti-static boots. Keep away from sources of ignition - No smoking.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from sources of ignition - No smoking. Avoid exposure to high temperatures or direct sunlight.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
ETHANOL	WEL	1000 ppm	1920 mg/m3			
METHANOL	WEL	200 ppm	266 mg/m3	250 ppm	333 mg/m3	Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

Shellac Sanding Sealer

RESPIRATORY EQUIPMENT

Avoid inhalation of vapours. Wear full face mask supplied with: Gas cartridge suitable for organic substances.

HAND PROTECTION

Use barrier creams to prevent skin contact. For prolonged or repeated skin contact use suitable protective gloves. PVC gloves are recommended. Nitrile gloves are recommended.

EYE PROTECTION

Avoid contact with eyes. Wear approved safety goggles. Eye wash facilities and emergency shower must be available when handling this product.

SKIN PROTECTION

Wear apron or protective clothing in case of splashes.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Viscous liquid		
SOLUBILITY	Soluble in water		
RELATIVE DENSITY	>1	VAPOUR PRESSURE	<110 kPa
FLASH POINT (°C)	<=21°C		

10 STABILITY AND REACTIVITY

STABILITY

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

11 TOXICOLOGICAL INFORMATION

INHALATION

Harmful by inhalation. Harmful: possible risk of irreversible effects through inhalation. Vapours may cause drowsiness and dizziness.

INGESTION

Harmful if swallowed. Harmful: possible risk of irreversible effects if swallowed.

SKIN CONTACT

Repeated exposure may cause skin dryness or cracking.

EYE CONTACT

Irritating to eyes.

HEALTH WARNINGS

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

TARGET ORGANS

Mucous membranes. Central nervous system. Respiratory system, lungs. Kidneys. Liver.

MEDICAL SYMPTOMS

Narcotic effect. Vapours may cause drowsiness and dizziness.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

There are no data on the ecotoxicity of this product. Do not allow to enter drains, sewers or watercourses.

WATER HAZARD CLASSIFICATION

WGK 1

Shellac Sanding Sealer

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Do not discharge into drains, water courses or onto the ground.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk).

14 TRANSPORT INFORMATION



UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT		
UN NO. ROAD	1263	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	TUNNEL RESTRICTION CODE	(D/E)
HAZARD NO. (ADR)	33 Highly flammable liquid (flash-point below 23°C).	ADR LABEL NO.	3
HAZCHEM CODE	•3YE	UN NO. SEA	1263
IMDG CLASS	3	IMDG PACK GR.	II
EMS	F-E, S-E	UN NO. AIR	1263
ICAO CLASS	3	AIR PACK GR.	II

15 REGULATORY INFORMATION

LABELLING



Harmful



Highly Flammable

CONTAINS

METHANOL

RISK PHRASES

R11	Highly flammable.
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R68/20/21/22	Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

SAFETY PHRASES

S2	Keep out of the reach of children
S16	Keep away from sources of ignition - No smoking.
S36/37	Wear suitable protective clothing and gloves.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.

Shellac Sanding Sealer

S7/9	Keep container tightly closed and in a well-ventilated place.
S23	Do not breathe vapour/spray.
S24	Avoid contact with skin.
S33	Take precautionary measures against static discharges.

UK REGULATORY REFERENCES

Health and Safety at Work Act 1974. Chemicals (Hazard Information & Packaging) Regulations.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

STATUTORY INSTRUMENTS

Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

16 OTHER INFORMATION

REVISION DATE 24/11/2009

REV. NO./REPL. SDS GENERATED 4

RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R37	Irritating to respiratory system.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.